



| TOLERANCES | | | |
|-------------|-----------|------------|-----------|
| fabrication | | machining | |
| X.XXX | +/- 0.015 | X.XXX | +/- 0.005 |
| X.XX | +/- 0.031 | X.XX | +/- 0.010 |
| X.X | +/- 0.031 | X.X | +/- 0.015 |
| fractional | +/- 0.031 | fractional | +/- 0.031 |

| | | | | | | | |
|---|--|-------------|-------------------|--|-----------------------|-----------------|--|
| THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY AND REMAINS THE EXCLUSIVE PROPERTY OF AXIOMATIC TECHNOLOGIES CORPORATION. THIS DRAWING MAY NOT BE USED, REPRODUCED IN WHOLE OR IN PART, NOR REVEALED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF AXIOMATIC TECHNOLOGIES CORPORATION. BY ACCEPTANCE OF THIS DRAWING, THE BEARER AGREES TO THESE CONDITIONS. | | | | AXIOMATIC TECHNOLOGIES CORPORATION 5915 WALLACE ST. MISSISSAUGA, ON CANADA L4Z1Z8 905-602-9270 | | | |
| MATERIAL ADC12 die cast aluminum | | DRAWN TF | DATE 7/15/2016 | TITLE Isolated 24-24V 125W DC Converter | | | |
| FINISH MIL-A-8625 type III class I hard anodized | | CHECKED | DATE | DWG REV D1 | DWG NO AX080900-MD | PART REV A | |
| | | APPROVED | DATE | SCALE full | PART NO AX080900 | SHEET 1 of 1 | |