







DETAIL C

SCALE 2: 1

DT15-12PA receptacle

mates with: **AX070105**

Mating plug kit is comprised of: DT06-12SA with 1 wedgelock (W12S) and 12 contacts (0462-201-16141). All field wiring should be suitable for the operating temperature range.



label detail

CONNECTOR PINOUT	
1 - BATT -	**7** - CAN2_HIGH
2 - NOT USED	**8** - CAN2_LOW
3 - CAN1_SHIELD	**9** - CAN2_SHIELD
4 - RS485_GND	**10** - CAN1_HIGH
5 - RS485_TX/RX+	**11** - CAN1_LOW
6 - RS485_TX/RX -	**12** - BATT +

PROPRIETARY
THE INFROMATION CONTAINED IN THIS DRAWING IS CONDIFENTIAL AND PROPRIETARY AND REMAINS THE EXCLUSIVE PROPERTY OF AXIOMATIC TECHNOLOGIES CORPORATION. THIS DRAWING MAY NOT BE USED, REPRODUCED IN WHOLE OR IN PART, NOR REVEALED TO OTHERS WITHOUT THE PRIOR WRITTEN CONSENT OF AXIOMATIC TECHNOLOGIES CORPORATION. BY ACCEPTANCE OF THIS DRAWING, THE BEARER AGREES TO THE THESE CONDITIONS.

AXIOMATIC TECHNOLOGIES CORPORATION
5915 WALLACE ST.
MISSISSAUGA, ON
CANADA L4Z1Z8
905-602-9270

TOLERANCES

fabrication		machining	
X.XXX	+/- 0.015	X.XXX	+/- 0.001
X.XX	+/- 0.031	X.XX	+/- 0.005
X.X	+/- 0.031	X.X	+/- 0.015
fractional	+/- 0.031	fractional	+/- 0.031

MATERIAL: cast aluminum with a neoprene gasket	DRAWN: TF	DATE: 13/08/2012	TITLE: Protocol Converter. SAEJ1939, CANopen, Modbus RTU
	CHECKED: DL	DATE:	DWG REV: D1 / DWG NO: AX140200-MD / PART REV: B
	APPROVED: DL	DATE:	SCALE: full / PART NO: AX140200 / SHEET: 1 of 1