



## DECLARATION OF CONFORMITY

**Application of Council Directive(s):** 2014/30/EU - The EMC Directive  
**Manufacturer's Name:** Axiomatic Technologies Corporation  
5915 Wallace Street  
Mississauga, Ontario Canada L4Z 1Z8  
**Equipment Type/Environment:** Power Gen Set Networked Controller  
**Trade Names/Model Nos:** RTD Temperature Scanner/AXRTD8, AXRTD8CO, 234-1645,  
JM171100, JM171101  
**Year of Manufacture:** 2012/2013/2014/2015/2016/2017/2018/2019/2020  
**Testing Facility:** Self-declared  
**File No.:** Elite Electronic Engineering Inc. AXRTD8 (Engineering Test Report No. 1200329-02  
and 1201612-02)  
**Records Maintained by:** Axiomatic Technologies Corporation  
5915 Wallace Street, Mississauga, ON  
Canada L4Z 1Z8  
TEL: 905-602-9270

### Standard(s) to which Conformity is Declared:

#### Emissions:

IEC 60533: 1999 (Table 3, Class B)  
Radiated Emissions (0.15 – 30 MHz: 80-50 dbuV/m; 30-100 MHz: 60-54 kbuV/m; 100-2000 MHz: 54 dbuV/m except 156-165MHz 24 dbuV/m)  
Conducted Emissions (10-150 kHz: 120-69 dbuV, 150-500 kHz: 79 dbuV, 0.5-30 MHz: 73 dbuV)  
Test set up and methods per:  
CISPR 16-1-1, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1: Radio disturbance and immunity measuring apparatus. 2010. Class A  
CISPR 16-1-2, Specification for radio disturbance and immunity measuring apparatus and methods – Part 2: Methods of measurement of disturbance and immunity. 2009. Class A  
CISPR 16-1-4. 2010  
CISPR 16-2-3. 2010

#### Immunity:

Conducted Susceptibility IEC 60533:1999 Table 4 and EN 61000-4-6 *Immunity to conducted disturbances, induced by radio-frequency fields*: 2009 Criteria A (150 kHz-80 MHz, 3 Vrms) Criteria A  
Radiated Susceptibility IEC 60533: 1999 Table 4 and EN 61000-4-3 *Radiated, radio-frequency, electromagnetic field immunity test*: 2010 (80 - 2,700 MHz; 10 V/m; 80% AM, 1kHz) Criteria A  
Conducted Low Frequency Interference per IEC 60533:1999 Table 4 and EN 61000-4-16 *Test for immunity to conducted, common mode disturbances in the frequency range 50 Hz to 10 kHz*: 2011 (2.8 Vrms, 0.05=10 kHz) Criteria B  
Electrical Fast Transients/Burst per IEC 60533:1999 Table 4 and EN 61000-4-4 *Electrical fast transient/burst immunity test*: 2004 (2 kV to power lines, 1kV to signal lines and communication lines, 300 s) Criteria B  
Slow Transient/Electrical Surge Test per IEC 60533:1999 Table 4 and EN 61000-4-5 *Surge immunity test*: 2006 (+/- 0.5 kV L/L, +/- 1 kV L/E) Criteria B  
Immunity to Electrostatic Discharge per IEC 60533:1999 Table 4 and EN 61000-4-2 *Electrostatic discharge immunity test*: 2009 (6kV contact discharge, 8kV air discharge) Criteria B

*I, the undersigned, hereby declare that the equipment specified above conforms to the above Directive and Standards.*

#### **Manufacturer**

**Amanda Wilkins**  
**Axiomatic Technologies Corporation**  
**January 31, 2020**  
**Mississauga, Ontario, Canada**

**Axiomatic Technologies Corporation**  
5915 Wallace Street, Mississauga, Ontario Canada L4Z 1Z8  
TEL: 1 (905) 602-9270 FAX: 1 (905) 602-9279 E-mail: [sales@axiomatic.com](mailto:sales@axiomatic.com)  
[www.axiomatic.com](http://www.axiomatic.com)